

DEUREX® F 6312 O

TECHNICAL INFORMATION

Chemical description: Oil-based dispersion based on micronized PTFE coated wax **DEUREX® F 6314 M**

Application: Oil-based Printing inks
- Offset printing inks (Sheetfed, Web offset, Heatset, Coldset)

Oil-based Wood Protection

Hot foil stamping

Properties:

- Excellent abrasion and scratch resistance
- Improved chemical, weather and heat resistance
- Good anti-blocking and slip properties
- Improved transparency and good overprintability

Solvent: Linseed oil

Technical data:

Colour:	White opaque
Form of delivery:	Liquid
Packaging:	Drum 190 kg, hobbock 25 kg

	Minimum	Maximum	Method
Particle size:		98 % < 12 µm	LV 09
Typical value:		50 % ~ 6 µm	
Drop point (wax):	110 °C	120 °C	LV 12 (DGF M-III 3)
Melting point (PTFE):	320 °C	340 °C	LV 5 (ASTM D4591)
Solid content*:	34.0 %	36.0 %	LV 6

* part of certificate of analysis

Processing:

- Stir well before usage
- Consume quickly after opening

Storage, shelf life:

- Store at temperatures between +5 °C and +35 °C
- Shelf life 6 month in closed original container, avoid frost

Alternative variants: We also make this product with your own oil and any other solid concentration

Alternative delivery forms: **DEUREX® F 6408 W** – Water-based dispersion, 98% < 8 µm
DEUREX® F 6314 M – Micronized powder, 98 % < 14 µm

Alternative products: **DEUREX® E 0912 O** – PE wax oil-based dispersion, 98% < 22 µm
DEUREX® T 3912 O – FT wax oil-based dispersion, 98% < 12 µm
DEUREX® F 6012 O – PTFE oil-based dispersion, 98% < 12 µm