

## DEUREX® A 2015 M

### TECHNICAL INFORMATION

<b>Chemical description:</b>	Bio-based micronized Ethylene-Bis-Steramid wax (EBS)		
<b>Benefits:</b>	<ul style="list-style-type: none"> <li>- Very high temperature stability (no yellowing)</li> <li>- Guaranteed maximum particle size and constant and narrow particle size distribution</li> </ul>		
<b>Applications:</b>	<u>Paints and coatings</u> <ul style="list-style-type: none"> <li>- Powder coatings</li> <li>- Industry- and wood coatings</li> </ul>		
	<u>Masterbatch</u>		
<b>Properties:</b>	<ul style="list-style-type: none"> <li>- Good grindability</li> <li>- No gloss reduction</li> <li>- Degassing agent</li> <li>- Good anti-blocking and slip</li> </ul>		
<b>Technical data:</b>	Colour:	White	
	Delivery form:	<b>DEUREX® A 2015 M</b> = Micronized powder	
		Minimum	Maximum
	Particle size*:	98 % < 15 µm	
	Typical value:	50 % ~ 6 µm	
	Drop point*:	142 °C	151 °C
	Penetration:	2 mm*10 <sup>-1</sup>	5 mm*10 <sup>-1</sup>
	Density (23 °C):	0.98 g/cm <sup>3</sup>	1.00 g/cm <sup>3</sup>
			Method
			ISO 13320
			ASTM D 3954
			ASTM D 1321
			ISO 1183
	* Part of certificate of analysis		
<b>Approvals:</b>	Food contact approvals		
<b>Alternative products:</b>	See <a href="https://www.deurex.com/productsearch/DEUREX-A-2015-M/">https://www.deurex.com/productsearch/DEUREX-A-2015-M/</a>		