

## DEUREX<sup>®</sup> A 26 P

### TECHNICAL INFORMATION

**Chemical description:**

Vegetable Erucamide wax

**Application:**

Plastics industry (e.g. PVC, PE and PP)

Paper Industry

- Defoamer for the production of paper

Metal processing

- Surface lubricant for metal production

Printing inks

- Improves the dye distribution
- Good overprintability and wet printing properties

Rubber industry

- Reduction of the tacks in CSM roller mixer
- Mold release agents
- Increases the abrasion resistance
- Reduction of sulphurization

**Properties:**

- Excellent slip
- Lubricant, release agent
- Very good Anti-blocking properties
- Processing aid
- Abrasion resistance
- Dust free

**Technical Data:**

Colour: Light yellow  
Consistencies: **DEUREX A 26 P** = Powder

	Minimum	Maximum	Method
Drop point*:	83 °C	95 °C	ASTM D 3954
Acid value*:		1 mg KOH/g	ASTM D 1386
Viscosity (140 °C):		12 mPas	ISO 3219
Penetration:		45.0 mm*10 <sup>-1</sup>	ASTM D 1321
Density (23 °C):	0.87 g/cm <sup>3</sup>	0.88 g/cm <sup>3</sup>	ISO 1183

\* Part of certificate of analysis

**Approvals:**

Food contact approvals

**Alternative products:**

See <https://www.deurex.com/productsearch/DEUREX-A-26-P/>