

## DEUREX® A 28 P

### TECHNICAL INFORMATION

- Chemical description:** Vegetable Stearamide wax
- Application:**
- Plastics industry
- Metal processing
- Surface lubricant for metal production
- Printing inks
- Improves the dye distribution
  - Good overprintability and wet printing properties
- Rubber industry
- Reduction of the tacks in CSM roller mixer
  - Mold release agents
  - Increases the abrasion resistance
  - Reduction of sulphurization
- Properties:**
- Lubricant
  - Release agent
  - Very good Anti-blocking properties
  - Slip
  - Processing aid
  - Dust free

**Technical Data:**

Colour: White  
Consistencies: **DEUREX® A 28 P** = Powder

	Minimum	Maximum	Method
Drop point*:	100 °C	110 °C	ASTM D 3954
Acid value*:		2 mg KOH/g	ASTM D 1386
Viscosity (140 °C)*:		12 mPas	ISO 3219
Penetration:	2.0 mm*10 <sup>-1</sup>	8.0 mm*10 <sup>-1</sup>	ASTM D 1321
Density (23 °C):	0.90 g/cm <sup>3</sup>	0.91 g/cm <sup>3</sup>	ISO 1183

\* Part of certificate of analysis

**Approvals:** Food contact approvals

**Alternative products:** See <https://www.deurex.com/productsearch/DEUREX-A-28-P/>