

DEUREX[®] B 66 A

TECHNICAL INFORMATION

Chemical description:	Micronized EBS wax, coated with Benzoin based on 50% BENZOIN Micro and 50% DEUREX[®] A 2015 M (EBS)		
Applications:	<u>Degassing agent for powder coatings</u>		
Benefits:	<ul style="list-style-type: none"> - 16 times larger surface than Benzoin, therefore better degassing - "B 66 A" replaces two raw materials, the Benzoin and EBS waxes in powder coating formulations 		
Properties:	<ul style="list-style-type: none"> - Effective and rapid degassing - No yellowing (< 230 °C) - Good printability of the powder coating remains - Good adhesion of labels remains 		
Technical data:	Colour:	Off-white	
	Delivery forms:	DEUREX[®] B 66 A	= Finest powder, 98% < 150 µm
		Minimum	Maximum
	Drop point*:	133 °C	139 °C
		ASTM D4591	
	Density (23 °C):	1.25 g/cm ³	1.35 g/cm ³
		LV 3 (DIN EN ISO 1183)	
	Shelf life:	12 months	
		(In closed, original containers in compliance with storage conditions)	
	* Part of certificate of analysis		
Safety:	This product is not classified as dangerous preparation according to Directive 1999/45/EC. It is not subject to labelling according to EC Directive 67/548/EEC and Regulation (EC) 1272/2008.		
Alternative products:	DEUREX[®] A 2015 M – Micronized EBS wax, 98% < 15 µm DEUREX[®] X 2010 M – Renewable vegetable EBS wax, 98% < 10 µm		