

MASTERWAX[®] ANTIBLOCK

Chemical description

Bio-based micronized wax additive for paints and coatings

Purpose

- One wax additive for ALL liquid paints and coatings
- Anti-blocking agent that avoids any kind of bonding
- Increasing the durability of coatings
- Anti-blocking agent for stackability of end products
- Reduction of cleaning cycles
- Reduction of the amount of additives used
- Increase in production capacity
- Reduction of outspec batches
 - Reducing the stickiness of the coatings
- Reduction of adhesion
- Increase in lubrication

Properties

- Improved blocking resistance, slip performance and abrasion compared to PE waxes and FT waxes
- Wax application rate can be reduced by 25-50%
- Scratch resistance similar to PTFE waxes
- Improved weather resistance (H₂O, UV, ozone, cold) compared to PE and FT waxes
- Low dust behaviour, free-flowing powder, easy to dose
- Significantly finer with 98% <15 µm compared to conventional micronised waxes
- Perfect price/performance ratio

Technical data

Colour:	White		
Delivery form:	Micronized powder		
	Minimum	Maximum	Method
Particle size:		98% <15 µm	ISO 13320
Typical particle size:		50 % ~ 6 µm	
Drop point (wax)*:	115 °C	130 °C	ASTM D 3954
Density (23 °C) (wax):	0.96 g/cm ³	0.98 g/cm ³	ISO 1183

* Part of certificate of analysis

Benefits

- Suitable for water-based and solvent-based paints and coatings
- Reduction of application quantity
- Reduction of production costs
- Avoidance of outspec batches

Packaging

- 15 kg box
- 660 kg pallet

This information corresponds to the current state of our knowledge and is intended to provide information about our product and its possible applications. Therefore, it is not intended to guarantee certain properties of the products or their suitability for a specific purpose. The recipient must take any existing industrial or commercial property rights into consideration. This current version of the data sheet replaces all previous versions.

© - Registered trademark of DEUREX