

DEUREX® EO 47 P

TECHNICAL INFORMATION

Chemical description: Oxidized HDPE wax

Production process: Wet Oxidation

Applications: Production of water based emulsions and dispersions for

- Textile industry (improved sewability and cutting of textiles, improves

machine lifetime)

Care products, polishes

- Coatings and inks (e.g. overprint varnishes)

- Leather & paper industry

Benefits: - White powder, transparent melt

Finer particle size compared to DEUREX® EO 47 K
 For the production of very fine and transparent emulsions

- Easier to emulsify than DEUREX® EO 46 P due to higher acid value

Properties: - Improves the surface properties including scratch resistance

by lowering the coefficient of friction High density and high drop point Excellent abrasion resistance

- High blocking resistance and UV stability

- Improves processing time and adhesion to substrate

- Improves slip

Technical data: Color: Off-white

Delivery form: **DEUREX EO 47 P** = Powder

	Minimum	Maximum	Method
Drop point:	132 °C	135 °C	ASTM D 3954
Acid value*:	33 mgKOH/g	37 mgKOH/g	ASTM D 1386
Penetration:		0.5 mm*10 ⁻¹	ASTM D 1321
Viscosity (140 °C)*:		1.600 mPas	ISO 3219
Density (23 °C):	0.97 g/cm ³	0.99 g/cm ³	ISO 1183

^{*} Part of certificate of analysis

Approvals: Food contact approvals

Alternative products: See https://www.deurex.com/productsearch/DEUREX-EO-47-P/

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.

© - registered trademark by DEUREX