

## DEUREX® T 1501 W

### TECHNICAL INFORMATION

- Chemical description:** Water-based emulsion of paraffin wax
- Applications:**
- Raw material for water-based coating systems
- Coatings, paintings and printing inks
- Concrete admixture
- Properties:**
- Excellent water repellency and waterproofing on wood, paper, textile
  - Very good blocking resistance
  - Improved UV & ozone protection
  - Increased surface slip
  - Increased scratch and abrasion resistance
  - Good anti-graffiti properties
- Processing:**
- Stir well before usage, consume quickly after opening
- Storage, shelf life:**
- Store at temperatures between +5 °C and +28 °C, Avoid frost
  - Shelf life 6 months in closed original container

**Technical data:**

Colour: White  
 Solid: Paraffin wax  
 Form of delivery: Liquid  
 Packaging: IBC 1,000 kg

	Minimum	Maximum	Method
Drop point (solid):	47 °C	55 °C	ASTM D 3954
Solid content*:	49 %	51 %	IR Moisture-Analyzer
Emulsifier system:	anionic/nonionic		
pH-value*:	8.0	10.0	pH-electrode

\* part of certificate of analysis

**Alternative products:**

See <https://www.deurex.com/productsearch/DEUREX-T-1501-W/>