



## BIOMER® 119 P

### TECHNICAL INFORMATION

|                                 |   |
|---------------------------------|---|
| <b>Product Family:</b>          | <a href="#">BIOMERE – biodegradable waxes</a>                             |
| <b>Product Description:</b>     | Lipide, non-polar, straight chains, bio-based                             |
| <b>Benefits:</b>                | Biodegradable high melting wax to prevent the formation of micro plastics |
| <b>Application, Properties:</b> | See <a href="http://www.DEUREX.com">www.DEUREX.com</a>                    |
| <b>Biodegradability:</b>        | Raw material is biodegradable according to the test method OECD 301 B     |

#### Technical Data:

Colour: Yellowish

|                  | Typical value | Method      |
|------------------|---------------|-------------|
| Drop point wax*: | 110 – 120 °C  | ASTM D 3954 |
| Acid value:      | 2 – 5 mgKOH/g | ASTM D 1386 |

#### BIOMER® 119 P

Form of delivery: Powder

*\*part of certificate of analysis*

**Storage, Shelf life:** **Solid form:** Dry storage. Store at temperatures (+5 °C to +28 °C)  
Shelf life: minimum 24 months

**Alternative Products:** **BIOMERE** – range of melting point from 60°C to 140°C  
See [www.DEUREX.com](http://www.DEUREX.com)