

## DEUREX® P 37 P

### TECHNICAL INFORMATION

<b>Chemical description:</b>	Polypropylene wax		
<b>Applications:</b>	<u>Paints and coatings</u> - Industrial coatings, decorative paints, furniture and parquett coatings  <u>Printing inks</u> - Gravure inks, overprint varnishes, screen printing inks, flexo printing inks  <u>Paper industry</u>  <u>Masterbatch</u>		
<b>Properties:</b>	- Lubricant, matting agent - Scratch resistance, improved anti-slip - Improved soft feel effect		
<b>Benefits:</b>	- High temperature resistance - Reduced pigment concentration due to high colour intensity		
<b>Technical data:</b>	Colour:	White	
	Delivery form:	DEUREX® P 37 P = Powder	
		Minimum	Maximum
	Drop point*:	145 °C	165 °C
	Acid value:		0 mg KOH/g
	Viscosity (180 °C)*:	100 mPas	200 mPas
	Penetration:		1 mm*10 <sup>-1</sup>
	Density (23 °C):	0,87 g/cm <sup>3</sup>	0,89 g/cm <sup>3</sup>
	*part of certificate of analysis		
<b>Approvals:</b>	Food contact approvals		
<b>Alternative products:</b>	See <a href="https://www.deurex.de/produkte/">https://www.deurex.de/produkte/</a>		