

DEUREX® EO 4519 ABS

TECHNICAL INFORMATION

Chemical description: Micronized oxidized HDPE-wax with built-in anti-blocking system (ABS)

Applications: Paints and coatings

Solvent and water based paints and coatings

Powder coatings, industrial coatingsWood, furniture and parquet coatings

- Can and coil coatings

Masterbatch

- For pigments which are difficult to disperse

Properties: - Excellent Anti-blocking

- Very good sandability

- High hardness

- Improved abrasion and scratch resistance

- Good Slip properties, reduction of the friction coefficient

- Improved anti-caking properties

Degassing agent for powder coatings

- Increases extruder output, improves flowability of the powder

Fast drying of paints and coatingsGloss-reducing properties in coatings

- Soft-feel effect in wood coatings

- PFAS, PTFE, VOC free

Benefits: - DEUREX® EO 45 probably the hardest wax in the world

- Guaranteed maximum particle size and constant and narrow

particle size distribution

Easily dispersible without lump or coagulate formation

- Free-flowing, non-sticking

Technical data: Colour: White

Delivery form: **DEUREX® EO 4519 ABS** = Micronized powder

Minimum Maximum Method Particle size*: 98 % < 19 um ISO 13320 Typical value: $50 \% \sim 8 \mu m$ Drop point*: 138 °C 143 °C **ASTM D 3954** Penetration: 1 mm*10⁻¹ 2 mm*10⁻¹ **ASTM D 1321** Density (23 °C): 0.97 g/cm³ 0.99 g/cm³ ISO 1183

Approvals: Food contact approvals

Alternative delivery form: See https://www.deurex.com/products/

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.

(B - registered trademark by DEUREX

^{*} Part of certificate of analysis